

Viacrete Wetshield

PRODUCT DESCRIPTION:

Viacrete Wetshield is a premium-grade, solvent-based sealer formulated to provide a long-lasting wet look and water–oil repellency on natural and engineered stones. It penetrates deeply into the stone’s micro-pores, enhancing the natural color and protecting the surface without forming any film. Ideal for both interior and exterior applications, Wetshield delivers excellent resistance to UV rays, stains, and weather exposure. Whether for honed, flamed, brushed, sandblasted, or polished finishes, Viacrete Wetshield enhances aesthetics while offering superior surface protection.

Technical Details

Property	Result
Appearance	Transparent, opalescent liquid
Density @ 25°C	0.95 g/cm ³
Standard Colour	Colourless
Coverage	20–30 m ² per litre (depends on porosity)
Shelf Life	24 months in sealed container
Application Method	Brush, sponge, cloth, or spray
Surface Dry Time	Few seconds (buff off excess)
Full Cure	24 hours

KEY FEATURES & BENEFITS

- ✓ Deep Penetration – Enhances stone from within without altering surface texture
- ✓ Wet Look Finish – Intensifies natural color for a richer appearance
- ✓ Water & Oil Resistant – Prevents stains from moisture, grease, and spills
- ✓ UV Stable – Will not yellow or degrade under sunlight
- ✓ Anti-Graffiti Resistance – Helps protect treated surfaces from markings
- ✓ Non-Film Forming – Allows stone to breathe naturally
- ✓ Durable Protection – Long-lasting in both indoor and outdoor conditions
- ✓ Fast Acting – Achieves full effect within 24 hours

RECOMMENDED USES

- ✓ Marble, granite, travertine, limestone, and sandstone
- ✓ Engineered stone and concrete agglomerates
- ✓ Polished, honed, flamed, brushed, and sandblasted finishes
- ✓ Indoor flooring, exterior cladding, countertops, and wall panels
- ✓ High-traffic zones requiring stain and weather resistance

Application Instructions

01. SURFACE PREPARATION

- ✓ Ensure the surface is completely dry, clean, and dust-free
- ✓ Avoid applying on damp or contaminated surfaces



Viacrete Wetshield

PACKAGING

Available in 1 L, 5 L, and 20 L containers
Sealed in solvent-resistant tins

SHELF LIFE & STORAGE

- ✔ Store in a cool, dry place, away from direct sunlight and heat sources
- ✔ Temperature range: 18°C to 25°C
- ✔ Shelf life: 24 months in sealed original packaging

LIMITATIONS

- ✔ Do not apply on wet or damp surfaces
- ✔ Excess product may result in sticky, glossy films if not wiped off properly
- ✔ Not suitable for waxy or previously sealed surfaces without surface preparation
- ✔ Avoid using in extremely hot or humid conditions
- ✔ Not a substitute for structural waterproofing in submerged areas

Application Instructions

02. APPLICATION

- ✔ Apply Viacrete Wetshield evenly using a brush, sponge, cloth, or spray
- ✔ Allow the surface to absorb the product naturally
- ✔ After a few seconds, remove any excess with a clean cloth to avoid sticky residues
- ✔ For best results, repeat the application after 10–15 minutes
- ✔ Avoid walking on treated floors for at least 24 hours

SAFETY PRECAUTIONS

- ✔ Use in well-ventilated areas
- ✔ Wear gloves and eye protection during application
- ✔ Avoid contact with skin or eyes; rinse immediately if exposed
- ✔ Keep away from heat, flame, and children
- ✔ Refer to product MSDS for full safety information